



P.O. Box 890907 • Oklahoma City, OK 73189
 Office: (405) 703-0034 • Toll Free: 844-703-0034 • Fax: (405) 703-0697
www.hawkeyedirectional.com

6.75" S2 (171 mm) 7-8 2.9 STAGE

	Hole Size	8½ (216 mm)	8¾ (222 mm)	9⅝ (251 mm)
		Degrees per 100 Feet (30m)		
DYNOMAX SERIES 2 MOTOR - ADJUSTABLE (ABH)	BEND ANGLE	Degrees per 100 Feet (30m)		
	0.39	2.4	2.6	—
	0.78	4.8	5.0	5.8
	1.15	7.1	7.3	8.1
	1.50	9.3	9.5	10.2
	1.83	11.3	11.5	12.3
	2.12	13.1	13.3	14.1
	2.38	14.8	14.9	15.7
	2.60	16.4	16.2	17.0
	2.77	17.6	17.3	18.1
	2.90	18.6	18.1	18.9
	2.97	19.1	18.5	19.3
	3.00	19.3	18.7	19.5
DYNOMAX SERIES 2 MOTOR - ADJUSTABLE (ABH)	BEND ANGLE	Degrees per 100 Feet (30m)		
	0.39	0.1	—	—
	0.78	3.0	2.3	—
	1.15	5.7	5.0	2.0
	1.50	8.3	7.6	4.5
	1.83	10.7	10.0	7.0
	2.12	12.9	12.2	9.1
	2.38	14.8	14.1	11.0
	2.60	16.4	15.7	12.6
	2.77	17.6	17.0	13.9
	2.90	18.6	17.9	14.8
	2.97	19.1	18.4	15.4
	3.00	19.3	18.7	15.6

Bottom Stab Ø = 1/4" under hole size

Top Stab Ø = 7.0625 inch

Bit Length = 11 inch

Adj. Ring Ø = 7.54 inch

This information is for reference only. Build rates are calculated on a theoretical, three point geometry. The three points are bit contact, kick pad contact and top of motor contact with the well bore. Actual rates are also affected by formation tendencies, WOB and other drilling parameters. Offset data should be used, when possible, to help determine the expected build rate for any motor configuration.